



Similar image
(Picture shows ADA910T)

RCBO 1P+N 6kA C-16A 30mA A Class

| | |
|---|-------------------------------|
| Architecture | |
| Neutral position | right |
| Number of protected poles | 1 |
| Number of poles | 2 P |
| Type of pole | 1P+N |
| Fixing mode | DIN rail type O (symmetrical) |
| Curve | C |
| Functions | |
| Concurrently switching N-neutral | yes |
| Sealable | yes |
| Compatibility | |
| Compatible with DIN rail mounting | yes |
| Controls and indicators | |
| With Contact position indicator | no |
| With fault indicator | yes |
| Connectivity | |
| Top connection alignment for modular devices | Aligned terminal |
| Bottom connection alignment for modular devices | Aligned terminal |
| Main electrical features | |
| Rated operational voltage Ue | 230 - 240 V~ |
| Type of supply voltage | AC |
| Voltage | |
| Dielectric strength value of power frequency | 2 kV |
| Rated insulation voltage | 500 V |
| Max operating voltage | 240 V |
| Rated impulse withstand voltage | 4000 V |

Electric current

| | |
|--|----------------|
| Rated residual operating current | 30 mA |
| Rated current | 16 A |
| Withstand not tripping on 8-20 ?s wave | 250 A |
| Breaking and opening capacity | 4500 A |
| min/maxi threshold value of the AC thermal operation | 1,13 / 1,45 In |
| Magnetic regulating current | 5 / 10 In |

Electric current / temperature

| | |
|----------------------|--------|
| Rating current -25°C | 18,5 A |
| Rating current -20°C | 18,3 A |
| Rating current -15°C | 18,1 A |
| Rating current -10°C | 17,9 A |
| Rating current -5°C | 17,7 A |
| Rating current 0°C | 17,4 A |
| Rating current 5°C | 17,2 A |
| Rating current 10°C | 17 A |
| Rating current 15°C | 16,7 A |
| Rating current 20°C | 16,5 A |
| Rating current 25°C | 16,2 A |
| Rating current 30°C | 16 A |
| Rating current 35°C | 15,8 A |
| Rating current 40°C | 15,6 A |
| Rating current 45°C | 15,4 A |
| Rating current 50°C | 15,2 A |
| Rating current 55°C | 15 A |
| Rating current 60°C | 14,8 A |
| Rating current 70°C | 10,9 A |

Current correction factors

| | |
|---|--|
| Correction factor of rating current for 2 devices placed 1 side-by-side | |
| Correction factor of rating current for 3 devices placed 0,95 side-by-side | |
| Correction factor of rating current for 4 and 5 devices 0,9 placed side-by-side | |
| Correction factor of rating current for 6 devices placed 0,85 side-by-side | |

Frequency

| | |
|-----------|-------|
| Frequency | 50 Hz |
|-----------|-------|

Power

| | |
|---------------------------|-------|
| Total power loss under IN | 5,2 W |
| Power loss per pole at In | 3,8 W |

Endurance

| | |
|--|------|
| Electric endurance in number of cycles | 2000 |
| Number of mechanical operations | 2000 |

Dimensions

| | |
|-----------------------------|-------|
| Depth of installed product | 68 mm |
| Height of installed product | 83 mm |
| Width of installed product | 35 mm |

Installation, mounting

| | |
|---|--------------------|
| Type of top connection for modular devices | with screw |
| Tightening torque | 2,1Nm |
| Type of top rail clip for modular devices | NA |
| Type of bottom rail clip for modular devices | plastic |
| Type of Bottom Connection for modular devices | Blconnect + bypass |
| Top removability for modular devices | no |
| Bottom removability for modular devices | yes |
| Suitable for flush-mounting | yes |
| 360° product mounting position | yes |

Connection

| | |
|--|------------------------|
| Connection cross-section at output with screw, for flexible conductor | 1 / 16 mm ² |
| Connection cross-section at output with screw, for massive conductor | 1 / 25 mm ² |
| Connection cross-section for rigid conductor, upstream terminals with screws | 1 / 25 mm ² |
| Connection cross-section of the access with screws, with flexible conductor | 1 / 16 mm ² |
| Cage clamp position | in line |
| Downstream cage clamp delivery status | opened |
| Upstream cage clamp delivery status | opened |
| Connection cross-section of input and output with screws, for massive conductors | 1 / 25 mm ² |
| Connection cross section of access and exit with screws, for flexible conductor | 1 / 16 mm ² |
| Nominal tightening torque bottom terminal | 2,1 Nm |
| Nominal tightening torque top terminal | 2,1 Nm |

Cable

| | |
|---|---------------------|
| Length of conductors used for the heating test (m) according to product standard | 1 m |
| Conductor cross-section used for heating test(mm ²) according to product standard | 2,5 mm ² |

Equipment

| | |
|---------------------------------------|-----|
| Can be accessorized | yes |
| Accept terminal cover | no |
| With transparent product label holder | yes |

Standards

| | |
|-------------------------|-----------------------------|
| Standard text | IEC 61009-1, AS/NZS 61009-1 |
| European directive WEEE | not concerned |

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Use conditions

| | |
|--|------------------|
| Degree of pollution according to IEC 60664 / IEC 60947-2 | 2 |
| Class of energy limitation I ² t | 3 |
| Altitude | 2000 m |
| Air humidity protection | for all climates |
| Storage/transport temperature | -25 70 °C |

temperatur

| | |
|--|---------|
| Temperature of calibration | 30 °C |
| Ambient air temperature during heating test according to the product standard | 23,1 °C |
| Max. admissible temperature on accessible parts (intended to be touched) | 63,2 °C |
| Max. admissible temperature on accessible parts (manual operating means) | 50,1 °C |
| Max. admissible temperature on access. parts (not touched for normal operation) | 84,1 °C |
| Max. admissible temperature on terminals | 73,2 °C |
| Temp.-rise limits for access. parts (toggle) according to product standard | 25 K |
| Temp.-rise limits for access. parts (not touched) according to product standard | 60 K |
| Temp.rise limits for access. parts (to be touched) according to product standard | 40 K |
| Temperature-rise limits for terminals according to the product standard | 65 K |
| Temperature-rise measured on accessible parts at In (manual operating means) | 10,1 K |
| Temperature-rise measured on access. parts at In (not touched normal operation) | 44,1 K |
| Temperature-rise measured on accessible parts at In (intended to be touched) | 23,2 K |
| Temperature-rise measured on terminals at In | 33,2 K |