

GENERAL INFO

FILTRATION AND ULTRAVIOLET ALL-IN-ONE UNIT WITH WEATHER COVER

Enjoy peace of mind with safe, bacteria-free water at every outlet in the house.

Suited to medium to large households, these systems are designed for both mains and rainwater supply. This unit features a weather protection cover that is suitable for outdoor installation and an anti-tamper & childproof lockable lid. It incorporates an additional filtration stage for extra contaminant removal and capacity.

FEATURES & BENEFITS

- Quick and easy plug-and-play installation.
- Reduces sediment, chemicals including chlorine, bad taste, odour and is highly effective in eliminating bacteria and parasites in your water.
- Kills 99.99% of E. coli, Giardia and Cryptosporidium cysts with Radfire™ ultraviolet technology, a natural purification process that's completely eco-friendly and chemical free.
- Turns your tank and mains water into pure, safe, delicious drinking water.
- Filtration and ultraviolet all-in-one unit.
- High strength aluminium bracket for durability.
- Designed for harsh climate.
- Equipped with a lamp count-down timer and alarm.
- Anti-tamper & childproof lockable lid.
- Anti-corrosion construction.
- Hinged lid for easy access for lamp change.



HYBRID-G12

10", 1 connection, max. flow: 60 Lpm


HYBRID-G13

20", 1 connection, max. flow: 120 Lpm

Ordering Code	HYBRID-G12	HYBRID-G13
Replacement parts and cartridges:		
Stage 1 filtration:	PLO5MP1	PLO5MP2
Stage 2 filtration:	CB05MP1	CB05MP2
Stage 3 filtration:	PX01MP1	PX01MP2
UV lamp, 46 W	RL6	RL6
Quartz sleeve:	RQS6	RQS6
Flow rate @40mJ/cm ² :	54 Lpm	54 Lpm
Flow rate @30mJ/cm ² :	70 Lpm	70 Lpm
Flow rate @16mJ/cm ² :	130 Lpm	130 Lpm
Connection:	1" BSP [25mm]	1" BSP [25mm]
Warranty:	3 years [^]	3 years [^]

Important Note: Use only genuine Puretec replacement cartridge. Flow rate @30mJ/cm² is the industry standard for drinking water.

DIAGRAM & FILTRATION TECHNOLOGY



WMTS103:2016
Certificate No. WM 74593
Australian Certification Services



Weather Protection & Anti-Corrosion Construction

The Hybrid G Series incorporates a weather cover for outdoor installations. The durable lightweight mounting bracket is made from coated aluminium to ensure no rusting.




Triple Stage Filtration with UV Protection


Incorporates an additional filtration stage for extra contaminant removal and capacity. Highly effective and efficient at removing dirt, rust, sediment, bad taste and odour in your water, providing good general purpose filtration.

PRODUCT DIMENSIONS Measurements in Millimeters (mm)

HYBRID G12



HYBRID G13



ADDITIONAL INFORMATION

Where the water being treated contains unusually high levels of dissolved solids particularly hard water, iron, manganese or biological organisms, a deposit build up on the quartz sleeve may occur over time. Maximum recommended parameters are as follows:

Iron:	less than 0.3 mg/L
Hydrogen Sulfide:	less than 0.05 mg/L
Suspended Solids:	less than 10mg/L
Manganese:	less than 0.05 mg/L
Hardness:	less than 110mg/L



- Note:**
1. No claims can be made based on the specifications and images in this document. The design, technology, colours, features and prices are subject to change.
 2. This document and all its contents are copyright protected. All rights are reserved, particularly alteration, translation and reproduction using electronic systems.
 3. Warranties in this document cover parts for the period stated and include cover for parts and labour for the first year where applicable, subject to approval. Plus 2 years parts only. Our Water Filtration Specialists can provide you with advice to suit your needs.