

## Product data sheet Characteristics

# P40RSM2-XW

Type of packing

Quantity per set

Pro Series, selector switch, 40M, 4 positions, marked Off-1-Off-2, 10 A, White



#### Main Range Pro Series Product or component Selector switch type Colour tint White

Polybag

Set of 20

#### Complementary

Device presentation	Mechanism with central plate	
Control type	Rotary knob	
Switch function	4 positions	
Marking	0 - 1 - 0 - 2	
Rated current	10 A	
[Ue] rated operational voltage	250 V	
Material	PC (polycarbonate) PA66 ABS (acrylonitrile butadiene-styrene)	
Fixing mode	By clips	
Surface finish	Glossy	
Surface treatment	Untreated	
Connections - terminals	Screw terminal	
Clamping connection capacity	1 x 1.54 x 1.5 mm² for rigid or stranded cable(s) 3 x 2.5 mm² for stranded cable(s) 1 x 4 mm² for stranded cable(s)	
Height	23 mm	
Width	23 mm	
Depth	32 mm	
Product weight	0.016 kg	

#### **Environment**

Ambient air temperature for operation	045 °C	
Relative humidity	1095 %	
Product certifications	RCM	

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	16.98 g	
Package 1 Height	1.6 cm	
Package 1 width	1.9 cm	
Package 1 Length	3.9 cm	