

Single phase 10 & 15A switched sockets

Part Numbers

Part Number	Description
W66SS310	10A 3 pin switch socket
W66SS315	15A 3 pin switch socket

Specification

Housing

IP	66
Colour	Light grey
Material - top	Polycarbonate
Material - back box	Polycarbonate
UV stabilised	Yes
Fixing screws	Stainless steel * 8
Gland size & qty	2*M20 + 1*M25

Switch Mechanism - Heavy duty

Current rating	20A
Switching poles	2
Rotation	90 deg
Voltage rating	250V AC
Terminal type	1 screw tunnel
Terminal diameter	7.4mm
Terminal depth	17mm
Maximum cable size	16mm ²
Test Standard	IEC947-3/AS3133
M rating (AS3133)	M100
Padlockable	Yes (8mm app)

Socket

Current rating	10/15A
Phases	1
For pin configuration	3 flat pins
Voltage rating	250V AC
Terminal type	Brass - 1 screw
Terminal size	4.5 x 3 x 10mmD
Maximum cable size	6mm ²
Test Standard	AS3112

Dimensions

Height (ex gland plugs)	197mm
Width	101mm
Depth - top of cover	67mm
Depth - top of handle	85mm



Approval/Compliance certification

Approval	RCM mark
----------	----------

For use with Plug top

W66SS310	use W66SP310
W66SS315	use W66SP315

Accessories included

Gland adapters	2
Base screw covers	4
Top screw covers	8 (loose) + 4 (spares)

Spare Components

Back box	W66B2S
Isolator	W66IS220LB
Socket 10A	W66US310LB
Socket 15A	W66US315LB