



Main

Product brand	Clipsal
Range	Iconic
Product or component type	Connected switched socket
Range compatibility	Wiser hub
Device presentation	Mechanism with fixing frame
Socket-outlet type	Twin switched socket-outlet
Socket number	2
Outlet poles configuration	2P + E
Outlet standard deviation	Australian

Complementary

Device mounting	Flush
Rated current	10 A
[Ue] rated operational voltage	240 V AC 50 Hz
Communication network type	Wireless Zigbee (2405...2480 MHz), 10 mW at < 50 m
Colour tint	White
Surface finish	Matt
Local signalling	LED
Control type	Rocker on/off switching By mobile application
Technology type	Bluetooth low energy
Memory description	Backup memory - date and time for 6 h Backup memory - program for indefinite period
Material	Plastic
Type of installation	Indoor installation

Environment

IP degree of protection	IP20
Relative humidity	5...90 % non-condensing
Standards	AS/NZS 3112 safety AS/NZS 60669.2.1 safety AS/NZS 60669.2.1 EMC AS/NZS 4268 radio

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.4 cm
Package 1 Width	9.5 cm
Package 1 Length	14.1 cm
Package 1 Weight	202 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	22.7 cm

Package 2 Width	26.4 cm
Package 2 Length	33.8 cm
Package 2 Weight	4.5 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	960
Package 3 Height	95 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	238 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information