# Product data sheet Characteristics

## 40N-RD

# Clipsal Iconic, LED Mechanism, Red



#### Main

| Wall                      |                              |  |
|---------------------------|------------------------------|--|
| Range of product          | Pro Series                   |  |
| Product or component type | Indicator module             |  |
| Device presentation       | Mechanism with central plate |  |
| Type of packing           | Polybag                      |  |

## Complementary

| Device mounting                | Clip with locking bar                        |  |
|--------------------------------|--|--|
| [Ue] rated operational voltage | 250 V  |  |
| Surface treatment              | Untreated                                    |  |
| Local signalling               | LED red for status                           |  |
| Material                       | PC (polycarbonate): housing<br>PA66: housing |  |
| Height                         | 23 mm  |  |
| Width                          | 23 mm  |  |
| Depth                          | 32 mm  |  |
| Net weight                     | 0.016 kg                                     |  |
|                                |  |  |

### **Packing Units**

| Unit Type of Package 1       | PCE     |  |
|------------------------------|---------|--|
| Number of Units in Package 1 | 1       |  |
| Package 1 Height             | 2.2 cm  |  |
| Package 1 Width              | 2.2 cm  |  |
| Package 1 Length             | 2.4 cm  |  |
| Package 1 Weight             | 16.98 g |  |