Product data sheet Characteristics

56C550-GY

Clipsal - 56 Series, Switched Socket Outlet, 500V, 50A, 5 Round PIN, IP66, 3 Pole, Surface Mount





Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	Grey (RAL 7035)

Complementary

Complementary		
Number of poles	5	
Plug, socket category	Low voltage	
Outlet standard deviation	Australian/New Zealand	
Plug, socket, control station shape	Straight	
Number of modules	3	
Number of power socket outlets	1 protective cover	
[In] rated current	50 A	
[Ue] rated operational voltage	500 V AC 50 Hz	
Poles description	3P + N + E	
Protection type	Without protection	
Device mounting	Surface	
Material	Polycarbonate: cover	
Contacts material	Pins: phosphor bronze	
Connections - terminals	Screw terminals cable(s) 1016 mm²	
Electrical connection	Industrial connector	
Depth	108 mm	
Width	101 mm	
Height	204 mm	
Targeted country	Australia	

Environment

Standards	AS/NZS 3133 AS/NZS 3123	
Ambient air temperature for operation	-2575 °C	
IP degree of protection	IP66 conforming to AS 60529	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.8 cm
Package 1 Width	11.0 cm
Package 1 Length	20.6 cm
Package 1 Weight	1.246 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile