

Product data sheet Characteristics

4RC425SI30

Clipsal MAX4, Residual current circuit breaker 4P 25 A 30 mA type A-SI 415 V



Main

Range	MAX4
Product or component type	Residual current circuit breaker (RCCB)
Product brand	Clipsal
Poles description	4P
Number of modules	4
[In] rated current	25 A
Earth-leakage sensitivity	30 mA
Earth-leakage protection class	Type A-SI (Super Immunised)

Complementary

[Ue] rated operational voltage	415 V AC	
[Uimp] rated impulse withstand voltage	6 kV	
Mounting support	DIN rail	
Size	81 x 72 x 75 mm conforming to DIN 43880	

Environment

Standards	AS/NZS 61008
IP degree of protection	IP40
Pollution degree	2
Ambient air temperature for operation	-540 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.7 cm	
Package 1 Width	9.5 cm	
Package 1 Length	8.1 cm	
Package 1 Weight	364.0 g	

Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Compliant EPEU RoHS Declaration	
Yes	
☑ China RoHS Declaration	
₫Yes	
Product Environmental Profile	
	Compliant E EU RoHS Declaration Yes China RoHS Declaration Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of these products for specific user applications. This characteristic is not integrated to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.