

### Product data sheet Characteristics

## 4RCBM210SI30

# Clipsal MAX4, RCBO 2 module 2P 10 A C curve 30mA Type A-SI 10000A



#### Main

Range	MAX4
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Product brand	Clipsal
Poles description	2P
Number of modules	2
[In] rated current	10 A
Curve code	С
Earth-leakage sensitivity	30 mA
Earth-leakage protection class	Type A-SI (Super Immunised)
Breaking capacity	10000 A

#### Complementary

[Ue] rated operational voltage	240 V AC
[Uimp] rated impulse withstand voltage	4 kV
Size	81 x 36 x 77.5 mm conforming to DIN 43880

#### Environment

Standards	AS/NZS 61009
IP degree of protection	IP20 IP40
Ambient air temperature for operation	-2540 °C

#### **Packing Units**

PCE	
1	
8.2 cm	
10.0 cm	
4.0 cm	
227.0 g	
_	1 8.2 cm 10.0 cm 4.0 cm

#### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	€ Yes	
Environmental Disclosure	Product Environmental Profile	
Halogen content performance	Halogen free plastic parts product	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of these products for specific user applications. This characteristic is not integrated to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.