

## Product data sheet

### Characteristics

# CLITPDB2EM

Clipsal Lighting, Batten Diffused LED,  
1200mm, Emerg



### Main

Range	Clipsal
Product name	TPDB Series
Product or component type	Batten light
Device application	Lighting
Battery type	LiFePO4

### Complementary

Type of installation	Indoor/outdoor
Operational power in W	40 W
Light source	LED
[Ue] rated operational voltage	240 V AC 50 Hz
Luminous flux	4000 lm
Bulb lifespan	30000 h
Colour	White
Colour temperature	4000 K
Autonomy	3 h
Charging time	16 h
Control type	Test button
Supply	Non-maintained
Device mounting	Surface
Mounting mode	Ceiling
IP degree of protection	IP20
Electrical insulation class	Class I
Length	1170 mm
Width	72.5 mm
Height	72 mm
Shape	Rectangular
Distance between centers	1170 mm
Net weight	2.2 kg





### Environment

Colour rendering index	R <sub>a</sub> =80
Ambient air temperature for operation	-10...45 °C
Relative humidity	10...95 %
Targeted country	Australia

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	7.7 cm
Package 1 Length	121.6 cm
Package 1 Weight	2.4 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	17.0 cm
Package 2 Width	17.4 cm
Package 2 Length	123.0 cm
Package 2 Weight	10.0 kg

## Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>