

### Product data sheet Characteristics

# L8R

## Clipsal MAX4, Mini Activelink 100 A 500 V 8 hole with cover front wiring Red



Main	
Range	MAX9
Product brand	Clipsal
Range of product	Blue Point
Product or component type	Active link

### Complementary

Cable cross section	16 mm²	
[ln] rated current	100 A	
[Ue] rated operational voltage	500 V	
Connector type	Screw terminals	
Number of mounting holes	8	

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	0.1 kg	

### Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.