

## Product data sheet Characteristics

# L6/25R

type

## Clipsal MAX4, Mini Active link 110 A 500 V 6 hole with cover Red



#### Main MAX9 Range Product brand Clipsal Range of product Blue Point Product or component Neutral link

## Complementary

Cable cross section	25 mm²	
[In] rated current	110 A	
[Ue] rated operational voltage	500 V	
Connector type	Screw terminals	
Number of mounting holes	6	

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.2 cm	
Package 1 Width	4.7 cm	
Package 1 Length	6.5 cm	
Package 1 Weight	0.09 kg	

### Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.