

Product data sheet Characteristics

CPL7000FLH-WE LED Panel, Airflow, 15W, 47dB

Main

Range of product	Airflow
Range	Airflow
Product brand	Clipsal
Product or component type	Fan, Light and Heater units
Product destination	Ceiling fitting
Device application	Duct
Main colour tint	White
Colour tint	White

Complementary

[Ue] rated operational voltage	230/240 V AC 50 Hz	
Air flow	400 m3/h	
Power consumption in W	1085 W	
Cut-out dimensions	616 x 325 mm	
Depth	190 mm	
Air discharge option	Downflow	
Noise level	47 dB	
Fan type	Centrifugal	
Light source	LED 15 W	
Heat dissipation	1000 W	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	39 cm	
Package 1 Width	40.5 cm	
Package 1 Length	71.5 cm	
Package 1 Weight	12.5 kg	
Unit Type of Package 2	PAL	
Number of Units in Package 2	8	
Package 2 Height	110 cm	
Package 2 Width	114 cm	
Package 2 Length	114 cm	
Package 2 Weight	115 kg	

Offer Sustainability

Packaging without single use plastic	No
Packaging made with recycled cardboard	No
REACh Regulation	☑REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes

RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1533

2