

Product data sheet Characteristics

5753L

PIR Occupancy Sensor, C-Bus Control and Management System, Flush Mount, 360 Degree

Main	
Range	C-Bus
Product brand	Clipsal
Product or component type	Occupancy sensor
Device application	Lighting
Product specific application	Staircase monitoring
Sensor type	PIR
Colour	White

Complementary

Protection type Creep zone protection Type of setting Light sensitivity adjustable Number of channels 1 Time delay range 01 s (switch-on) Detection face Lateral: 7.5 m Frontal: 7.5 m Movement detection area 15 m Horizontal detection angle 0360 ° Duty cycle 1080 min Material Plastic Device mounting Flush Mounting height 2.4 m	o in promortary		
Number of channels Time delay range 01 s (switch-on) Detection face Lateral: 7.5 m Frontal: 7.5 m Movement detection area 15 m Horizontal detection angle 0360 ° Duty cycle 1080 min Material Plastic Device mounting 1 Number of channels 1 1 1 1 1 1 1 1 1 1 1 1 1	Protection type	Creep zone protection	
Time delay range 01 s (switch-on) Detection face Lateral: 7.5 m Frontal: 7.5 m Movement detection area 15 m Horizontal detection angle 0360 ° Duty cycle 1080 min Material Plastic Device mounting Flush	Type of setting	Light sensitivity adjustable	
Detection face Lateral: 7.5 m Frontal: 7.5 m Movement detection area 15 m Horizontal detection angle 0360 ° Duty cycle 1080 min Material Plastic Device mounting Flush	Number of channels	1	
Frontal: 7.5 m Movement detection area 15 m Horizontal detection angle 0360 ° Duty cycle 1080 min Material Plastic Device mounting Flush	Time delay range	01 s (switch-on)	
Horizontal detection angle 0360 ° Duty cycle 1080 min Material Plastic Device mounting Flush	Detection face		
Duty cycle 1080 min Material Plastic Device mounting Flush	Movement detection area	15 m	
Material Plastic Device mounting Flush	Horizontal detection angle	0360 °	
Device mounting Flush	Duty cycle	1080 min	
	Material	Plastic	
Mounting height 2.4 m	Device mounting	Flush	
	Mounting height	2.4 m	

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.529 cm
Package 1 Width	12.706 cm
Package 1 Length	16.538 cm
Package 1 Weight	200 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	30 cm
Package 2 Width	43.2 cm
Package 2 Length	22 cm
Package 2 Weight	2420 g
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	95 cm
Package 3 Width	80 cm

Package 3 Length	120 cm	
Package 3 Weight	47720 g	

Offer Sustainability

Packaging without single use plastic	No
Packaging made with recycled cardboard	Yes
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	44

Life Is On