



COOPER SE7082TC - 16W

16 watt, IP65 LED commercial bunker (cross frame) luminaire, selectable CCT, IK10 rated, ceiling or wall mount

Application

A decorative architectural solution for commercial exteriors

Design Specifications

- Robust die-cast aluminium body, durable black or silver powder coat finish
 - Stainless steel allen screws
 - High efficiency LED optics
 - Integral constant current non-dimmable LED driver
 - Selectable CCT 3000 / 4000 / 5700K
 - UV stabilized opal polycarbonate diffuser, IK10, IP65 performance
- Product selections compliant to AS/NZS2293
Emergency Lighting & Exit Signs are located in the [exterior emergency section](#)





Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **TRAILING EDGE**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**



Technical Specification


Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7082TC/BK	240	16	1100/1150/1100	3000/4000/5700	80
	SE7082TC/SL	240	16	1100/1150/1100	3000/4000/5700	80

Beam Angle (°)	Mass (kg)	Diameter (mm)	Dim (mm)	Body Colour
100	1.66	265	95(H)	BLACK
100	1.66	265	95(H)	SILVER

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SE7082TC



Photometric Data

Unit: cd C0/C180 C90/C270

SE7082L SL WW at 3000K

