Product data sheet Characteristics

WSC227/2-RG SWITCHED SOCKET TWIN WEATHER PROTECTED 10A 250V





Main

Colour	Resistant grey
Product brand	Clipsal
Range of product	Weathershield

Complementary

Control type Sliding type ON/OFF button Number of gangs 2 gangs Pin number 3 Number of power socket outlets 2 Mounting position Horizontal Fixing mode By screws Local signalling Without light indicator Material Plastic [Ue] rated operational voltage 250 V AC [In] rated current 10 A Length 115 mm Width 85 mm	Complementary		
Number of gangs 2 gangs Pin number 3 Number of power socket outlets 2 Mounting position Horizontal Fixing mode By screws Local signalling Without light indicator Material Plastic [Ue] rated operational voltage 250 V AC [In] rated current 10 A Length 115 mm Width 85 mm	Colour code	RG	
Pin number 3 Number of power socket outlets 2 Mounting position Horizontal Fixing mode By screws Local signalling Without light indicator Material Plastic [Ue] rated operational voltage 250 V AC [In] rated current 10 A Length 115 mm Width 85 mm	Control type		
Number of power socket outlets Mounting position Horizontal By screws Local signalling Without light indicator Material [Ue] rated operational voltage [In] rated current Length Width 85 mm	Number of gangs	2 gangs	
Mounting position Horizontal Fixing mode By screws Local signalling Without light indicator Material Plastic [Ue] rated operational voltage 250 V AC [In] rated current 10 A Length 115 mm Width 85 mm	Pin number	3	
Fixing mode By screws Local signalling Without light indicator Material Plastic [Ue] rated operational voltage 250 V AC [In] rated current 10 A Length 115 mm Width 85 mm	Number of power socket outlets	2	
Local signalling Without light indicator Material Plastic [Ue] rated operational voltage 250 V AC [In] rated current 10 A Length 115 mm Width 85 mm	Mounting position	Horizontal	
Material Plastic [Ue] rated operational voltage 250 V AC [In] rated current 10 A Length 115 mm Width 85 mm	Fixing mode	By screws	
[Ue] rated operational voltage250 V AC[In] rated current10 ALength115 mmWidth85 mm	Local signalling	Without light indicator	
[In] rated current 10 A Length 115 mm Width 85 mm	Material	Plastic	
Length 115 mm Width 85 mm	[Ue] rated operational voltage	250 V AC	
Width 85 mm	[In] rated current	10 A	
	Length	115 mm	
Fixing center 84 mm	Width	85 mm	
	Fixing center	84 mm	

Environment

IP degree of protection	IP53
Standards	AS/NZS 3112:approval number S/1

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	