Product data sheet Characteristics

438-TR SOCKET CORD EXTENSION 0.75X1SQ FLEXIBLE 250V



Main

Range of product	Standard Series
Colour	Transparent
Product brand	Clipsal
Quantity per set	Set of 1
Cover type	Complete housing

Complementary

Marking Without marking Local signalling Without light indicator Material PVC (polyvinyl chloride) [In] rated current 10 A [Ue] rated operational voltage 250 V AC Depth 71 mm Diameter 43 mm	Colour code	TR	
Material PVC (polyvinyl chloride) [In] rated current 10 A [Ue] rated operational voltage 250 V AC Depth 71 mm	Marking	Without marking	
[In] rated current 10 A [Ue] rated operational voltage 250 V AC Depth 71 mm	Local signalling	Without light indicator	
[Ue] rated operational voltage 250 V AC Depth 71 mm	Material	PVC (polyvinyl chloride)	
Depth 71 mm	[In] rated current	10 A	
	[Ue] rated operational voltage	250 V AC	
Diameter 43 mm	Depth	71 mm	
TO THIS	Diameter	43 mm	

Environment

LIMIOIIIIEII	
Standards	AS/NZS 3112
	AS 3100
	AS 3109
	AS/NZS 3122:approval number S/1